



Fenwick™ Heavy Duty Series

Fenwick™ Heavy Duty Series

The Fenwick heavy duty chair comfortably supports workers up to 400 pounds with a 24" seat, heavy-duty mechanism, frame, platform construction, and dual-density cushions on both the seat and back. It includes solid ergonomics such as back height adjustment, seat height adjustment, height and width adjustable armrests, and sliding seat depth adjustment (to fit leg length).

290 High Back Chair Specifications



290-27R-WT Standard WT armrests included



290-01HDSS-WT - Heavy duty, 400 lb weight capacity

High Back Heavy Duty Multi-Tilter - Pneumatic, soft descent seat height adjustment. Backrest height adjustment. Independent, infinite position back and seat angle adjustment with tilt lock control. Tilt-tension adjustment. Front activated seat depth adjustment (seat slider). Forward seat tilt lock control. Dual density heavy duty foam on seat and backrest cushions. Recommended for 24hr and heavy duty applications. **Height and width adjustable arms with soft polyurethane arm caps are standard and included.**

290-27RHD-WT Heavy duty, 400 lb weight capacity

High Back Heavy Duty Synchro - Pneumatic, soft descent seat height adjustment. Ratchet type backrest height adjustment. Independent, infinite position back and seat angle adjustment with tilt lock control. Tilt-tension adjustment. Front activated seat depth adjustment (seat slider). Dual density seat and backrest cushions. Recommended for 24hr and heavy duty applications. **Height and width adjustable arms with soft polyurethane arm caps are standard and included.**

Seat			Back		Shipping	
Height	Width	Depth	Height	Width	Lbs	Cube
19-23.75"	24"	20"	24"	19"	75	13

294 High Back Chair Specifications



294-01HDSS-WT Standard WT armrests included



294-01HDSS-WT - Heavy duty, 400 lb weight capacity

Executive Back Heavy Duty Multi-Tilter - Pneumatic, soft descent seat height adjustment. Backrest height adjustment. Independent, infinite position back and seat angle adjustment with tilt lock control. Tilt-tension adjustment. Front activated seat depth adjustment (seat slider). Forward seat tilt lock control. Dual density heavy duty foam on seat and backrest cushions. Recommended for 24hr and heavy duty applications. **Height and width adjustable arms with soft polyurethane arm caps are standard and included.**

294-27RHD-WT Heavy duty, 400 lb weight capacity

High Back Heavy Duty Synchro - Pneumatic, soft descent seat height adjustment. Ratchet type backrest height adjustment. Independent, infinite position back and seat angle adjustment with tilt lock control. Tilt-tension adjustment. Front activated seat depth adjustment (seat slider). Dual density seat and backrest cushions. Recommended for 24hr and heavy duty applications. **Height and width adjustable arms with soft polyurethane arm caps are standard and included.**

Seat			Back		Shipping	
Height	Width	Depth	Height	Width	Lbs	Cube
19-23.75"	24"	20"	30"	21"	78	13